

DIAMOND BRUME



Model: DIAMOND BRUME

Size: 70X40 cm

Thickness: 10 mm

Material: PORCELANIC TILE

Technical Features		Referencial Normative
Manufacture Process	Single Fired Tiles	Dry Pressing ceramic tile
Thickness (mm.)	10	UNE EN ISO 10545 Part 2
Length. Width , density, straightness, flatness.	Fulfills the requirements applied to each model defined in the normative UNE-EN-14411 for Group Bla	UNE EN ISO 10545 Part 2
Water absorption	E<0.5 %	UNE EN ISO 10545 Part 3
Resistance to flexion (N/mm.2) and breaking strength (N)	>35 >1300	UNE EN ISO 10545 Part 4
Resistance to superficial abrasion (Glazed Tiles)	3	UNE EN ISO 10545 Part 7
Resistance to scratch (Mohs)	7	UNE EN ISO 10545 Part 8
Resistance to termal clash	Resists Test	UNE EN ISO 10545 Part 9
Resistance to crack	Resists Test	UNE EN ISO 10545 Part 11
Frost Resistance	Resists Test	UNE EN ISO 10545 Part 12
Anti-slip	Class 0	UNE ENV 12633:2003

Chemical Resistance		
Domestic cleaning products	GA	UNE EN ISO 10545 Part 13
Swimming Pool Salt	GA	
Acids and bases (low concentration)	GLA/GHA	
Resistance to stains	Class 5	UNE EN ISO 10545 Part 14

Colors of this piece on this technical card are illustrative and can differ from the real piece.