

HARMONY

22,3x22,3 CUBAN SILVER ARROW/22,3

PRODUCT USE

INTERIOR EXTERIOR FLOOR & WALL TILES
SHOWER WALL

TONALITY VARIATION

Ligera
Bajo

PACKING

,99 M2/CJ 24,00 Kg/CJ 0 CJ/PI 0 Kg/PI

PRODUCT DESCRIPTION






INSTALATION RECOMENDATION AND PRODUCT CARE

It is recommended that installation be performed by a qualified professional. We don't recommend use of adhesives based on epoxy resin. Respect the drying time set by the manufacturer of the adhesive used.

Fill joints thoroughly using fine grain size materials, which will not scratch the surface of the part. Remove with water and a sponge all the excess product before it sets.

Adhesive recommended for the product: Mapei products

For initial and daily cleaning use a damp cloth and mild soap is recommended. Avoid using abrasive cleaners and media products acidic or alkaline cleaning.

Body Technical Specifications		Test Method	Standard Value	Pass/Fail
	Frost resistance	ISO 10545-12	RESIST	Yes
Surface Technical Specifications		Test Method	Standard Value	Pass/Fail
	Acids and alkalis resistance	ISO 10545-13	GLA/GLA	Yes
	Crazing resistance	ISO 10545-11	RESIST	Yes
	Staining resistance	ISO 10545-14	5	Yes
	Surface Quality	ISO 10545-2	> 95 %	Yes