

Ceracasa, s.a. www.ceracasa.com



Alcora, February 12, 2020

## **QUALITY CERTIFICATE:**

Material: Enamelled porcelain.

Models: BLUEMOON.

Finish: GLOSS

Formats: 49.1x98.2 cm.rect.

CERACASA, S.A. certifies the above referenced models are manufactured to meet the standards UNE-EN 14411, for ceramic tiles, pressed dry with very low water absorption (Group Bla). It is manufactured in the production facilities of Ceracasa, in Castellon (Spain), to meet the first quality standards and have the following technical characteristics, as recorded in their catalogues:

> DETERMINATION OF WATER ABSORPTION, (BOIL METHOD) (Standard UNE-EN-ISO 10545-3) Average water absorption: < 0.3 %

RESISTANCE to STAINS. ISO 10545-s-14:

Class 5

DETERMINATION of chemical resistance • s/ISO 10545-13; 2017:

A - Products for household cleaning:

B. - Additives for swimming pools water: A.

C - Acids and alkalis (low concentration): LA

D. - Acids and alkalis (concentrated):

DETERMINATION OF THE RESISTANCE TO SCRATCHING OF THE SURFACE Mohs hardness: 4 (UNE 67-1011 M:1992)

DETERMINATION OF FROST RESISTANCE (s/UNE EN ISO 10545-12:1992)

Resist







## DETERMINATION OF IMPACT RESISTANCE (s/UNE EN ISO 10545-5)

Resist

DETERMINATION OF DIMENSIONS AND SURFACE APPEARANCE (Standard UNE-EN-ISO 10545-2). It meets the standard.

- 1.-length and width: conforms to.
- 2 thickness: meets standard.
- 3. straightness of sides: conforms to.
- 4 orthogonality: meets standard.
- 5. surface flatness: conforms to.
- 6. surface quality: conforms to

The high-gloss ceramic materials, due to the same characteristics of intense brightness, present more easily to have stripes derived from their use.

It is advisable to extreme the cleaning and protection measures during the placement and the use of dirt retaining elements (rugs or mats), in the access areas from the outside to 'limit the presence of abrasives, like grit and gravel from the outside.

Likewise, the aging resistance of such models of porcelain and lost color by the action of sunlight is negligible. This family of products are stable and do not undergo photochemical degradation when exposed to the light radiation emitted by the Sun. The color is stable for the lifetime of the product.

These products are in conformity with the provisions of Annex G to the norma UNE-EN-14411 : 2013 "Ceramic tiles. Definitions, classification, characteristics and marking". (Group Bla,  $E \le 0.5$  %).

Felipe Sierra Grau

**Quality Dept** 





