

BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP ARTIC (PRC)30X60RC/ARG06_S |
| Size (cm.): | 30X60 RECTIFIED |
| Colour: | ARTIC |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 298 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 48 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | $E \leq 0.5$ | UNE EN ISO 10545-3 |
| Braking strenght (S): | $> 1300N$ | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | $\geq 35 N/mm^2$ | |
| Resistance to superficial abrasion (PEI): | 4 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:


| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP EARTH (PRC)30X60RC/ARG06_S |
| Size (cm.): | 30X60 RECTIFIED |
| Colour: | EARTH |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 298 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 48 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | E ≤ 0.5 | UNE EN ISO 10545-3 |
| Braking strenght (S): | > 1300N | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | ≥35 N/mm2 | |
| Resistance to superficial abrasion (PEI): | 4 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:


| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP SMOKE (PRC)30X60RC/ARG06_S |
| Size (cm.): | 30X60 RECTIFIED |
| Colour: | SMOKE |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 298 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 48 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | E ≤ 0.5 | UNE EN ISO 10545-3 |
| Braking strenght (S): | > 1300N | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | ≥35 N/mm2 | |
| Resistance to superficial abrasion (PEI): | 3 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:

| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP ARTIC RC(PRC)60X60/ARG03_S |
| Size (cm.): | 60x60 RECTIFIED |
| Colour: | ARTIC |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 600 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 24 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | $E \leq 0.5$ | UNE EN ISO 10545-3 |
| Braking strenght (S): | $> 1300N$ | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | $\geq 35 N/mm^2$ | |
| Resistance to superficial abrasion (PEI): | 4 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:


| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP EARTH RC(PRC)60X60/ARG03_S |
| Size (cm.): | 60x60 RECTIFIED |
| Colour: | EARTH |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 600 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 24 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | $E \leq 0.5$ | UNE EN ISO 10545-3 |
| Braking strenght (S): | $> 1300N$ | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | $\geq 35 N/mm^2$ | |
| Resistance to superficial abrasion (PEI): | 4 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:

| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





BASIC CHARACTERISTICS:

| | |
|--------------|---|
| Pieces name: | KALKSTEN LAP SMOKE RC (PRC)60X60/ARG3_S |
| Size (cm.): | 60x60 RECTIFIED |
| Colour: | SMOKE |
| Series name: | KALKSTEN |
| Family: | GLAZED PORCELAIN COLOUR BODY |

TECHNICAL CHARACTERISTICS:

| | | |
|--|----------------------------|--------------------|
| Fabrication process: | Dry pressed ceramic tile | |
| Absorption group (ISO 13006): | BIa UGL | |
| Finished: | Lapatto | |
| Work size (mm): | 600 x 600 x 10 | |
| Aesthetic classification and shade variations: | V.2 | |
| Diferent design number: | 24 | |
| Facial dimension range and surface quality: | Complies with the standard | UNE EN ISO 10545-2 |

PHYSICAL CHARACTERISTICS:

| | | |
|---|----------------------------|--------------------|
| Water absorption: | $E \leq 0.5$ | UNE EN ISO 10545-3 |
| Braking strenght (S): | $> 1300N$ | UNE EN ISO 10545-4 |
| Flexural tensile strenght (N/mm2): | $\geq 35 N/mm^2$ | |
| Resistance to superficial abrasion (PEI): | 3 | UNE EN ISO 10545-7 |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8 |

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:





| | | |
|--|----------------------------|----------------------|
| Thermic shock resistance: | Complies with the standard | UNE EN ISO 10545-9 |
| Moisture expansion: | Complies with the standard | UNE EN ISO 10545-10 |
| Crazing resistance: | Complies with the standard | UNE EN ISO 10545-11 |
| Durability; Freeze - thaw cycle: | Complies with the standard | UNE EN ISO 10545-12 |
| Scratch hardness according to Mohs: | 9 | UNE EN 67-101-92 |
| Slipperiness: | Anti-slip Class 2 | UNE - ENV 12633:2003 |

CHEMICAL PROPERTIES:

| | | |
|---|-----------|---------------------|
| Resistance to chemicals and pool treatment products: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases: | Class GHA | |
| Resistance to Low concentration acids and bases: | Class GLA | |
| Resistance to staining: | Class 5 | UNE EN ISO 10545-14 |

CE MARKING:

| | |
|-----------|---------------------|
| CE | 004CPR-PR/11-4-2013 |
|-----------|---------------------|

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Certifications:

