



Calle Melilla 1 Pol. Ind Colomer APD 194  
12200 Onda (Castellón) Spain  
C.I.F. B12915211

**BASIC CHARACTERISTICS:**



<b>Pieces name:</b>	MICROTECH GREY (AZJ) 30X90
<b>Size(cm):</b>	30X90 RECTIFIED
<b>Colour:</b>	GREY
<b>Series name:</b>	MICROTECH
<b>Family:</b>	WALL TILE WHITE BODY

**TECHNICAL CHARACTERISTICS:**

<b>Fabrication process:</b>	Single-fired porous white-body tile	
<b>Absorption group (ISO 13006):</b>	BIII	
<b>Finish:</b>	GL	
<b>Surface Finish:</b>	Matt	
<b>Body:</b>	White body	
<b>Work size (mm):</b>	300X900X8,7	
<b>Aesthetic classification and shade variations:</b>	V.2	
<b>Facial dimension range and surface quality:</b>	Complies with standard	UNE EN ISO 10545-2

**PHYSICAL CHARACTERISTICS:**

<b>Water absorption:</b>	E>10%	UNE EN ISO 10545-3
<b>Braking strenght (S):</b>	>600N	UNE EN ISO 10545-4
<b>Flexural tensile strenght (N/mm2):</b>	≥15 N/mm2	
<b>Lineal thermal expansion between 20º to 100ºC</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance:</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance:</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle:</b>	N/A	UNE EN ISO 10545-12

**CHEMICAL PROPERTIES:**

<b>Resistance to chemicals and pool treatment products:</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases:</b>	Minimum HB	
<b>Resistance to low concentration acids and bases:</b>	Minimum LB	
<b>Resistance to staining:</b>	Complies with the standard	UNE EN ISO 10545-14

**CE MARKING:**

	003CPR-A/11-4-2013
--	--------------------

**NOTAS IMPORTANTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed.  
Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process.  
Document with commercial information and cannot be used either judicially or administratively without the express premission of Mykonos Mosaic S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.


16/07/2020

JEFE DE PRODUCTO



Calle Melilla 1 Pol. Ind Colomer APD 194  
12200 Onda (Castellón) Spain  
C.I.F. B12915211

**BASIC CHARACTERISTICS:**



<b>Pieces name:</b>	MICROTECH LIGHT (AZJ) 30X90
<b>Size(cm):</b>	30X90 RECTIFIED
<b>Colour:</b>	LIGHT
<b>Series name:</b>	MICROTECH
<b>Family:</b>	WALL TILE WHITE BODY

**TECHNICAL CHARACTERISTICS:**

<b>Fabrication process:</b>	Single-fired porous white-body tile	
<b>Absorption group (ISO 13006):</b>	BIII	
<b>Finish:</b>	GL	
<b>Surface Finish:</b>	Matt	
<b>Body:</b>	White body	
<b>Work size (mm):</b>	300X900X8,7	
<b>Aesthetic classification and shade variations:</b>	V.2	
<b>Facial dimension range and surface quality:</b>	Complies with standard	UNE EN ISO 10545-2

**PHYSICAL CHARACTERISTICS:**

<b>Water absorption:</b>	E>10%	UNE EN ISO 10545-3
<b>Braking strength (S):</b>	>600N	UNE EN ISO 10545-4
<b>Flexural tensile strength (N/mm<sup>2</sup>):</b>	≥15 N/mm <sup>2</sup>	
<b>Lineal thermal expansion between 20° to 100°C</b>	Complies with the standard	UNE EN ISO 10545-8
<b>Thermic shock resistance:</b>	Complies with the standard	UNE EN ISO 10545-9
<b>Crazing resistance:</b>	Complies with the standard	UNE EN ISO 10545-11
<b>Durability; Freeze - thaw cycle:</b>	N/A	UNE EN ISO 10545-12

**CHEMICAL PROPERTIES:**

<b>Resistance to chemicals and pool treatment products:</b>	Complies with the standard	UNE EN ISO 10545-13
<b>Resistance to high concentration acids and bases:</b>	Minimum HB	
<b>Resistance to low concentration acids and bases:</b>	Minimum LB	
<b>Resistance to staining:</b>	Complies with the standard	UNE EN ISO 10545-14

**CE MARKING:**



003CPR-A/11-4-2013

**NOTAS IMPORTANTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed.  
Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process.  
Document with commercial information and cannot be used either judicially or administratively without the express premission of Mykonos Mosaic S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

16/07/2020

JEFE DE PRODUCTO