

CONTROL LABORATORY

TECHNICAL CHARACTERISTICS

Date

11-September-2.020

MODEL:	FORMAT	45 x 45
BRIANA MARINE	CLAY TYPE:	Red PORCELAIN

WATER ABSORPTION (UNE-EN ISO 10545-3)							
E ≤ 0,5							
PRE	PRESENTING POROSITY GRAZE (Visual examination and/or under the microscope)						
		High Poros	sity		Low Porosity	X	No Porosity
PLA	NA	RITY					
	X	Normal			Concave		Convex
BEH	BEHAVIOR OF THE PART TO CUT						
	X	Ok			Bad		
DETERMINATION OF THE RESISTANCE TO THE SLIDE with Equipment of Test							
of P	of Pendulum of Friction (UNE-ENV 12633)						
			R_d 39	9			Class 2
FROST RESISTANCE (EN ISO 10545-12) Resists							
SCRATCH HARDNESS ACCORDING TO MOHS (EN-101) 8							
ABRASION RESISTANCE (Method PEI) (UNE-EN ISO 10545-7)							
		PEI	IV				

CHEMICAL RESISTANCE (Ácidos, Bases y Productos domésticos de limpieza)							
Ammonium chloride solution	Class GA	Sodium hypochlorite solution	Class GA				
(UNE-EN ISO 10545-13)		(UNE-EN ISO 10545-13)					
3% Solution of	Class	18% Solution of	Class				
hydrochloric acid (UNE-EN ISO 10545-13)	GLA	hydrochloric acid (UNE-EN ISO 10545-13)	Test method available				
Weak solution of potassium hydroxide (UNE-EN ISO 10545-13)	Class GLA	Concentrated potassium hydroxide solution (UNE-EN ISO 10545-13)	Class Test method available				
Citric acid solution (UNE-EN ISO 10545-13)	Class GLA	Lactic acid solution (UNE-EN ISO 10545-13)	Class Test method available				

RESISTENCE TO STAINS		
Agent green-red spots on light oil (UNE-EN ISO 10545-14)	Class	4
Iodine solution (UNE-EN ISO 10545-14)	Class	4
Olive oil (UNE-EN ISO 10545-14)	Class	4