



PRODUCT TECHNICAL CHARACTERISTICS

PRODUCT TYPE:	Dry pressed ceramic tile $0.5\% < Eb \leq 3\%$
GROUP:	B1b
USE:	Interior and exterior floors and walls
MODEL:	LILYA
FORMAT:	19,8X22,8 cm
COLOR:	SERIE-COTTO HEX-WHITE HEX-DECO TAUPE HEX-DECO COTTO HEX-DECO BLUE HEX

<u>TRIAL</u>	<u>Normative</u>	<u>Requirements Minima</u>	<u>BESTILE</u>	
Dimensions	ISO10545-2	LENGTH $\pm 0.6\%$ (max. $\pm 2.0\text{mm}$)	228	
		WIDTH $\pm 0.6\%$ (max. $\pm 2.0\text{mm}$)	198	
		THICKNESS $\pm 0.5\text{mm}$	10	
Water absorption	ISO10545-3	$0.5\% < Eb \leq 3\%$	0,93	
Breaking Strength in N (Thickness $\geq 7.5\text{ mm}$)	ISO10545-4	1100	2710	
Modulus of rupture N/mm ²	ISO10545-4	30	54	
Resistance to surface abrasion PEI Class	ISO10545-7	DECLARED VALUE	CLASS:	
COTTO HEX PEI III-WHITE HEX PEI IV-DECO TAUPE HEX PEI III				
DECO COTTO HEX PEI III-DECO BLUE HEX III				
Frost resistance	ISO10545-12	PERFORM	PERFORM	
Thermal shock	ISO10545-9	PERFORM	PERFORM	
Slip resistance	UNE-41901:2017EX (pendulum)	DECLARED VALUE	CLASS: 1 RD: 27	
Chemical resistance:	ISO10545-13			
a) Acids		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
b) Alkalis		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
c) Household products and salts for swimming pools.		GB	GA	
Stains	ISO10545-14	3	5	

Date

09/05/2023

RESPONSIBLE

JUAN MANUEL GIMENO

FINISHED PRODUCT LABORATORY