



PRODUCT TECHNICAL CHARACTERISTICS

PRODUCT TYPE:	Dry pressed porcelain tile 0.5% $<Eb \leq 3\%$
GROUP:	B1b
USE:	Interior and exterior walls
MODEL:	CAMDEN
FORMAT:	6,5X20 cm
COLOR:	ALL COLORS

<u>TRIAL</u>	<u>Normative</u>	<u>Requirements Minima</u>	<u>BESTILE</u>	
Dimensions	ISO10545-2	LENGTH $\pm 0.6\%$ (max. $\pm 2.0\text{mm}$)	65	
		WIDTH $\pm 0.6\%$ (max. $\pm 2.0\text{mm}$)	200	
		THICKNESS $\pm 0.5\text{mm}$	9,5	
Water absorption	ISO10545-3	0.5% $<Eb \leq 3\%$	1,16	
Breaking Strength in N (Thickness $\geq 7.5\text{ mm}$)	ISO10545-4	1100	2232	
Modulus of rupture N/mm ²	ISO10545-4	30	57	
Frost resistance	ISO10545-12	PERFORM	PERFORM	
Thermal shock	ISO10545-9	PERFORM	PERFORM	
Chemical resistance:	ISO10545-13			
a) Acids		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
b) Alkalis		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
c) Household products and salts for swimming pools.			GB	GA
Stains	ISO10545-14	3	5	

Date

09/05/2023

RESPONSIBLE

JUAN MANUEL GIMENO

FINISHED PRODUCT LABORATORY